



TRANSCENDENCIAS COMERCIALES S.L.

HC-3000 Electronic

The Electronic HC-3000 technical specifications are:

- Digital display with messages that relate the events that may occur during the length of the session
- Minimum installation required
- Automatic system for water ozonization, built in the machine
- Automatic for session preparation
- Automatic disinfecting system
- Automatic digital temperature safety system 20°C and 40°C
- Automatic pressure gauge from 0 to 200 mbar
- Automatic pressure safety at 100 mbar
- Comfortable and accessible system for gathering samples
- Total shutdown system
- Digital output control, with security system
- Liter session counter
- Irrigation time clock
- Device for oxygen access
- Active carbon filter of 5 microns
- Innovative design
- Transportable
- Operating control of the unit using two different systems:
 - Remote control device
 - An easily accessible front panel



HC-2000 Automatic

The Automatic HC-2000 technical specifications are:

- Innovated design
- Wheels for easier installation
- Remote control and front panel (independent operating)
- Automatic pressure safety at 100 mbar
- Regulatable pressure gauge from 0 to 200 mbar
- Automatic temperature safety at 22°C and 40°C
- Digital thermostat
- High sensitivity fuses against circuit overload
- Irrigation liter counter, with lighted display
- Irrigation time counter, with lighted display
- Emergency shutdown system
- Automatic disinfection
- Polipropilene filters
- A system of collection of samples for analysis
- Device for introduction of therapeutic solutions, salt water, oxygen, ozone
- UV lamp: after flowing through the activated charcoal filters, the water is exposed to Ultra-Violet light, which ensures the elimination of bacteria and viruses
- Chromotherapy
- Height level regulable



The Manual HC-1 technical specifications are:

- Innovated design
- Wheels for easier installation
- Easy of handling
- Automatic pressure safety at 100 mbar
- Regulable pressure gauge from 0 to 200 mbar
- Automatic temperature safety 40°C
- Digital thermostat
- Flow regulator from 0 to 150 l/h
- High sensitivity fuses against circuit overload
- Cleaning and disinfection system
- Deposit for disinfectant
- Activated carbon filters
- Device for introduction of therapeutic solutions, salt water, oxygen, ozone
- UV lamp: after flowing through the activated charcoal filters, the water is exposed to Ultra-Violet light, which ensures the elimination of bacteria and viruses
- Chromotherapy
- Height level regulable

HC-1 Manual



Have
a Healthy
Colon





transcom

TRANSCENDENCIAS COMERCIALES S.L.

COLON HYDROTHERAPY



LARGE SIZE



SMALL SIZE

BIOCOMPATIBILITY TEST RESULTS

An independant laboratory study was conducted to determine bio-compatibility on the component of our kits, not only the speculum but also in the hoses. The laboratory was looking for harmful chemicals and toxicity that would be leached from the plastics itself. There was no findings of resins or toxicity found that could be derived by contact from this material.



DESINFECTION

Our speculums are disinfected with "Tego 51" following AENOR NF T 72161 Norms, with a content of microbitics amphoters, active vs HBV and HIV viruses.

BOX OF 75 UNITS

Incorporating a new universal waste hose Model "Copolymer 103"

FEATURES

- Bulb style - Patent n° 385628
- Large and small size available
- 48" waste hose
- Designed for easier insertion and graater client comfort
- 1/4" inflow hoses available
- Thumb tab longer for easier handling
- Obturator designed for easier handling
- Lubricant packet included (net wt. 3g)

THE NEW
HC-KIT ★
BULB STYLE

PATENT USA N° 385628
PATENT N° 9302226-9302227



Have a Healthy Colon

OUR NEW SPECULUM IS MADE IN TRASLUCID POLYPROPILENE

LARGE SIZE

SMALL SIZE

